



KBT600XE

Hood, Decorative wall hood, Universal, Stainless steel, 60 cm, A

INTENSIVE EXTRACTION

A powerful intensive speed can be selected when quick extraction is needed, whether you're creating a sizzling stir fry or a preparing an aromatic curry, even the strongest cooking odours will be removed in no time.

CLEAN AIR

The 24h air exchange function makes the hood work for 10 minutes every hour at very low speed and therefore without noise for a total of 24 hours in order to purify the air of the house, with low energy impact.



TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 60 cm • Extraction: Expulsion • Electronic control: Yes •

EAN code: 8017709286613

AESTHETICS

Colour: Stainless steel • Finishing: Brushed • Aesthetics: Universal • Design: T flat • Material: Stainless steel • Type of steel:

Brushed

PROGRAMS / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • 24h air filter function: Yes • Time-setting options: Automatic switch-off

CONTROLS

Control setting: Electronic buttons

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light power: 1,3 W • Light color temperature scale (°K): 3000 °K • Free outlet maximum capacity: 820 m³/h • Motor power: 230 W • No. of filters: 2 • Anti-grease filters: Aluminium • Filter replacement indicator: Yes • Minimum distance from GAS hob: 650 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 500 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): A • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEChood): 53 KWh/year • Fluid Dynamic Efficiency (FDE): 29.8 • Lighting Efficiency (LE): 70.4 lux/W • Grease Filtering Efficiency (GFE): 79.7 % • Air flow at minimum speed (Qmin): 261 m³/h • Maximum extraction rate: 473 m³/h • Intensive extraction rate: 686 m³/h • Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 48 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 63 dB(A) • Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost): 71 dB(A) • Power consumption in stand-by mode (Ps): 0.23 W • Time increase factor (F): 0.9 • Energy Efficiency Index per first cavity: 52.0 • Measured air flow rate at best efficiency point (Qbep): 395 m³/h • Measured air pressure at best efficiency point (Qbep): 451 Pa • Measured electric power input at best efficiency point (Wbep): 159 W • Normal Power of the light system (Wl): 3 W • Average illumination of the light on the cooking surface (Emiddle): 156 lux • Sound power level at highest setting (Lwa): 70 dB(A)

ELECTRICAL CONNECTION

Nominal power: 230 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

OPTIONAL ACCESSORIES

SPEED 1

Extraction rate IEC 61591: 260 m³/h • Noise level IEC 60704-2-13: 49 dB(A) • Power: 132 W

SPEED 2

Extraction rate IEC 61591: 358 m³/h • Noise level IEC 60704-2-13: 57 dB(A) • Power: 152 W

SPEED 3

Extraction rate IEC 61591: 473 m³/h • Noise level IEC 60704-2-13: 64 dB(A) • Power: 175 W

SPEED 4

INTENSIVE SPEED

Extraction rate (IEC 61591): 686 m³/h • Noise level IEC 60704-2-13: 72 dB(A) • Power: 222 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 520x600x450 • Width: 600 mm • Depth (mm): 450 mm • Product Height (mm): 520 mm • Net weight (kg): 12.800 kg

ACCESSORIES INCLUDED

Tube reduction: Yes

OPTIONAL

KITFCKBT: Accessories, HoodsKITFCKBTR: Accessories, Hoods

