N 50, Built-under double oven, Stainless steel J1ACE2HNOB







Included accessories

2 x combination grid, 1 x universal pan

Optional accessories

Z11AB15A0 Baking tray, non-stick ceramic coated

Z11CB10E0 Baking tray, grey enamelled

Z11CR10X0 Baking and roasting grid (standard)

Z11GT10X3 Glass roasting dish, 5,4l

Z11TI15X0 Cliprails

Built under double oven - twice as flexible, twice as fast - bake or roast multiple dishes at the same time.

- $\sqrt{}$ EasyClean this special cleaning aid provides uncomplicated, energy-saving cleaning of the oven interior.
- $\sqrt{\,}$ LCD-Display simple, straightforward with large characters for clear reading
- $\sqrt{\,}$ Clip-on Rail easily removed and installed telescopic rails for flexible use on all shelf levels

Features

Technical Data

Color / Material Front : Stainless steel

Construction type : Built-in Integrated Cleaning system : No Dimensions : 717 x 594 x 550

Dimensions of the packed product (HxWxD) (mm) : $790 \times 690 \times 660$

Control Panel Material : Glass Door Material : Glass Net weight (kg) : 47.391 Usable volume of cavity (I) : 47

 ${\it Cooking method: Conventional\ heat,\ Full\ width\ grill,\ Hot\ Air,\ Hotair}$

gentle, Hot air grilling, Pizza setting Oven control : mechanical

Number of interior lights : 1 Approval certificates : CE, VDE EAN code : 4242004221982 Energy efficiency rating : A

Energy consumption per cycle conventional (2010/30/EC) : 0.84 Energy consumption per cycle forced air convection (2010/30/EC) :

0.71

Energy efficiency class (2010/30/EC) - cavity 2 : B

Energy consumption per cycle conventional - cavity 2 (2010/30/EC) :

0.83

Energy efficiency index (2010/30/EC): 94.7

Energy efficiency index cavity 2 (2010/30/EC): 120.3

Connection rating (W): 5300

Current (A): 25 Voltage (V): 220-240 Frequency (Hz): 50

Plug type: fixed connection, no plug





Features

• LCD Display (White)

Features

- Control panel lock
- Interior halogen light
- Cavity volume: 34 Litre
- Door hinge small cavity: bottom
- Cavity (inner surface) top: Enamel grey
- EasyClean
- Full glass inner door
- 1 Clip rail, Stop function
- Cavity (inner surface) bottom: enamel grey
- Door hinge big cavity: Drop down door

Top oven additional features

- Oven with 4 heating methods: Top/bottom heat, Full surface grill, Small area grill, Bottom heat
- \bullet Temperature range 50 °C 275 °C


Main oven additional features


• 2 x combination grid, 1 x universal pan

Performance/technical information

- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 717 mm x 594 mm x 550 mm
- \bullet Please refer to the dimensions provided in the installation manual







measurements in mm

If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	39	40
Full-surface induction hob	49	50
Gas hob	29	40
Electric hob	29	32

