


Serie | 2, Electric hob, 60 cm, Black PKE61RAA8B



The glass-ceramic radiant hob: makes cooking and cleaning especially easy.

- The handy ChildLock locks the control panel to prevent accidental changes in settings.

Technical Data

Product name/family : Cooking zone ceramic
Construction type : Built-in
Energy input : Electric
Total number of positions that can be used at the same time : 4
Required niche size for installation (HxWxD) : 45 x 560-560 x 490-500 mm
Width of the appliance : 592 mm
Dimensions : 45 x 592 x 522 mm
Dimensions of the packed product (HxWxD) : 100 x 750 x 590 mm
Net weight : 7.5 kg
Gross weight : 8.2 kg
Residual heat indicator : Separate
Location of control panel : Hob front
Basic surface material : Ceramic
Color of surface : Black
Approval certificates : CE, Eurasian, VDE
Length of electrical supply cord : 100 cm
EAN code : 4242005280384
Electrical connection rating : 6400 W
Voltage : 220-240 V
Frequency : 50; 60 Hz



4 242005 280384

Serie | 2, Electric hob, 60 cm, Black PKE61RAA8B

The glass-ceramic radiant hob: makes cooking and cleaning especially easy.

Flexibility of cooking zones

- Cooking zone front left: 145 mm, 1.2 KW
- Cooking zone rear left: 180 mm, 2 KW
- Cooking zone rear right: 145 mm , 1.2 KW
- Cooking zone front right: 180 mm, 2 KW

Usage convenience

- TouchSelect basic: control the power with imprinted +/- touch buttons.
- Variable 9-stage power settings for each zone: precisely adapt the heat with 9 power levels.
- Quick Stop: quickly switch off a cooking zone with one longer touch.

Design


- 60 cm: space for 4 pots or pans.
- Frameless design

Safety

- Control panel lock: prevent unintended activation of the hob.
- Main on/off switch: switch off all cooking zones at the touch of a button.
- Power on indicator light: indicates if the hob is heating.
- Automatic safety shut off: for safety reasons, heating stops after a preset time if not used (possible to customise).

Installation

- Dimensions of the product (HxWxD mm): 45 x 592 x 522
- Required niche size for installation (HxWxD mm) : 45 x 560 x (490 - 500)
- Min. worktop thickness: 16 mm
- Connected load: 6.4 KW
- Power cord: 1 m, Cable included



A: Minimum distance from the hob cut-out to the wall.
B: Recessed depth
C: With fitted oven underneath min. 20, possibly more; see space requirements for the oven.