

Serie | 6, Induction hob, 90 cm, Black PXX275FC1E











The panorama FlexInduction hob allows you to conveniently place your pots and pans next to each other.

- **DirectSelect:** Direct, simple selection of the desired cooking zone, power and additional functions.
- FlexInduction Zone: Get more flexibility by combining the cooking zones into one big zone for placing small pots and large cookware.
- **PerfectFry:** For perfect browning of roasted foods thanks to sensor control with 4 power levels.
- ComfortProfil: Elegant, appealing design with bevelled front and metal strips on the side.
- PowerBoost: Up to 50% more power for faster heating.

Technical Data

Product name/family:

Cooking zone ceramic

Construction type:

Built-in

Energy input:

Electric

Total number of positions that can be used at the same time: 4

Required niche size for installation (HxWxD):

51 x 880-880 x 330-330

Width of the appliance : 916 Dimensions : $51 \times 916 \times 353$

Dimensions of the packed product (HxWxD) (mm):

126 x 1031 x 472

Net weight (kg): 14.615 Gross weight (kg): Residual heat indicator: Separate Location of control panel: Hob front Basic surface material: Ceramic Color of surface: Black Approval certificates: AENOR, CE Length of electrical supply cord (cm): 110 4242002854458 EAN code: Electrical connection rating (W): 7400 Voltage (V): 220-240 Frequency (Hz): 60; 50





Serie | 6, Induction hob, 90 cm, Black PXX275FC1E

The panorama FlexInduction hob allows you to conveniently place your pots and pans next to each other.

Design

- Profile trim (front facette with side trim)
- 90 cm: space for 4 pots or pans.

Flexibility of cooking zones

- 2 Flex zones: use cookware of any shape or size anywhere within the 40cm long zone.
- Cooking zone front left: 210 mm, 200 mm, 2.2 KW (max. power 3.7 KW)
- Cooking zone rear left: 210 mm, 200 mm, 2.2 KW (max. power 3.7 KW)
- Cooking zone rear right: 210 mm, 200 mm , 2.2 KW (max power 3.7 KW)
- Cooking zone front right: 200 mm, 210 mm, 2.2 KW (max. power 3.7 KW)

Usage convenience

- DirectSelect: directly control the power with the imprinted touch bar.
- Variable 17-stage power settings for each zone: precisely adapt the heat with 17 power levels (9 main levels and 8 intermediate levels).
- Timer for all zones
- : switches off the cooking zone at the end of the time set (e.g. for boiled eggs).
- Timer shows how long the cooktop is in use : an alarm sounds at the end of the time set (e.g. for pasta).

Time saving & efficiency

- PowerBoost function for all zones
 boil water faster thanks to 50% more energy than at the highest standard level.
- QuickStart function: when switching on, the hob automatically selects the cooking zone with cookware (when placed on a zone whilst the hob is off).
- ReStart function: in case of unintentional switch-off, this feature restores all previous settings by switching on the hob again within 4 seconds.

Cooking assistance

 4 frying levels: prevents overcooking with the automatic temperature regulation of the integrated sensor.

Safety


- 2 stage residual heat indicator for each zone: indicates which cooking zones are still hot or warm.
- Control panel lock: prevent unintended activation of the hob.
- Freeze function: wipe overboiled liquids without unintentionally changing settings (blocking all touch buttons for 30 seconds).
- Main on/off switch: switch off all cooking zones at the touch of a button.
- Automatic safety shut off: for safety reasons, heating stops after a preset time if not used (possible to customise).
- Energy consumption display: shows the electricity consumption of the last cooking process.

Installation

- Dimensions of the product (HxWxD mm): 51 x 916 x 353
- Required niche size for installation (HxWxD mm) : $51 \times 880 \times (330 330)$
- Min. worktop thickness: 16 mm
- Connected load: 7.4 KW
- Power management options for 16A, 13A or 10A connection: limit the maximum power if needed (depends on fuse protection of electric installation).
- Power cord: 1.1 m, Cable included




Serie | 6, Induction hob, 90 cm, Black PXX275FC1E




① Ventilation gap must be present


All measurements in mm




- A: Minimum distance from the hob cut-out
- Recessed depth
 The clearance between the surface of the worktop and the top of the front of the oven must be 30 mm. See space

The worktop into which the hob is installer must withstand loads of approx. 60 kg; suitable substructures must be used if required.







①
Ventilation gap must be present.