N 50, Built-in oven, 60 x 60 cm, Stainless steel B1ACE4HN0B





Α



Optional accessories

Baking tray, non-stick ceramic coated
Baking tray, grey enamelled
Baking and roasting grid (standard)
3 level telescopic rails, full ext
Cliprails

Neff CircoTherm $\ensuremath{\mathbb{G}}$ - the unique hot-air system for simultaneous baking and roasting on up to 3 levels.

- $\sqrt{\rm CircoTherm^{\odot}}$ Smart hot-air solution that lets you bake on up to three levels at once.
- $\sqrt{\rm \ LCD-Display}$ simple, straightforward with large characters for clear reading
- $\sqrt{}$ Cliprails Place dishes exactly where you want them in your oven.

Features

Technical Data

Color / Material Front : Stainless steel Construction type : Built-in Integrated Cleaning system : Catalytic partial, Hydrolytic Min. required niche size for installation (HxWxD) : 585-595 x 560-568 x 550 mm Dimensions : 595 x 594 x 548 mm Dimensions of the packed product (HxWxD) : 675 x 690 x 660 mm Control Panel Material : Glass Door Material : Glass Net weight : 32.3 kg Usable volume of cavity : 71 | First cavity material : Other Oven control : mechanical Number of interior lights : 1 Length of electrical supply cord : 120 cm EAN code : 4242004225034 Number of cavities (2010/30/EC) : 1 Energy efficiency rating : A Energy consumption per cycle conventional (2010/30/EC) : 0.97 kWh/cycle Energy consumption per cycle forced air convection (2010/30/EC) : 0.81 kWh/cycle Energy efficiency index (2010/30/EC) : 95.3 % $Connection\ rating: 2990\ W$ Fuse protection : 13 A Voltage : 220-240 V Frequency : 60; 50 Hz Plug type : no plug (electrical connection by electrician) Included accessories : 2 x combination grid, 1 x universal pan





Features

Design

- LCD Display (White)
- Bar handle
- 4 shelf positions
- Cavity inner surface: enamel grey

Features

- Control panel lock
- Heating up indicator Automatic start
- Interior halogen light

Cleaning

- EcoClean Direct : back panel
- EasyClean

Programmes/functions

- Oven with Multifunction oven with 6 cooking functions: heating methods: CircoTherm[®], Top/bottom heat, Circo-roasting, Full surface grill, CircoTherm[®] intensive, CircoTherm[®] gentle
- Cooling fan

Accessories

- 1 Clip rail, Stop function
- 1 x universal pan, 2 x combination grid

Performance/technical information

• Energy efficiency rating (acc. EU Nr. 65/2014): A Energy consumption per cycle in conventional mode:0.97 kWh Energy consumption per cycle in fan-forced convection mode:0.81 kWh

Number of cavities: Main cavity Heat source: electrical Cavity volume:71 litre

- Total connected load electric: 2.99 KW
- 120 cm Cable length
- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 595 mm x 594 mm x 548 mm
- Niche dimension (hxwxd): 585 mm 595 mm x 560 mm 568 mm x 550 mm
- Please refer to the dimensions provided in the installation manual

N 50, Built-in oven, 60 x 60 cm, Stainless steel B1ACE4HNOB



≥ 20

60

(**B**)

≥ 550 /

560

≥

1

535

1

585+10

570

4

548

Dimensioned drawings Measurements in mm 560+8 (A) 180 min. 550 405 min. 600 96 19,5 595 min. 20 405 ġ ≤ 50 96 594 535 595 Space for max 50 570 appliance A: 19.5 mm B: Space for appliance connection 320 x 115 mm connection 548 320 x 115 594 ماله measurements in mm 19.5 25 595 max. 487.5 7.5 548 measurements in mm Installation with a hob. For recessed depth, see hob dimensional drawing Min. distance: Induction hob: 5 mm Gas hob: 5 mm 600 570 min. Electric hob: 2 mm 7.5 measurements in mm