

iQ700, Built-in oven, 60 x 60 cm, Black HB776G1B1B









Included accessories

2 x combination grid 1 x universal pan

Optional accessories

HZ913003	Glass roasting dish, 5,4 L
HZ636000	Glass pan
HZ634000	Baking and roasting grid (standard)
HZ631070	Baking tray, anthracite enamelled
HZ538000	varioClip rail
HZ531010	Baking tray, non-stick ceramic coated

UZO1EOO2 Class reacting dish E 41

Shorten your cooking time thanks to fast preheat, coolStart and activeClean. And remote control your oven from anywhere with Home Connect.

- ✓ TFT-Touchdisplay Plus Smooth-touch navigation for simple and intuitive operation.
- ✓ Oven Assistant with Voice Control Intuitively set the right programme.
- ✓ humidClean Plus For fast cleaning dirt is softened beforehand by vaporizing soapy water. It can then be removed more easily.
- ✓ Home Connect with Remote Control and Monitoring Unlock the full potential of your smart oven.
- ✓ cookControl Plus Pre-installed settings for excellent results.

Feature

Technical Data

Color / Material Front : Black Construction type : Built-in

Integrated Cleaning system: Pyrolytic+Hydrolytic

Min. required niche size for installation (HxWxD) : $585-595 \times 560-568$

x 550 mm

Dimensions: 595 x 594 x 548 mm

Dimensions of the packed product (HxWxD): 670 x 680 x 670 mm

Control Panel Material : Glass Door Material : Glass Net weight : 38.2 kg Usable volume of cavity : 71 l Oven control : electronic Number of interior lights : 1

Length of electrical supply cord: 120 cm

EAN code: 4242003901908 Number of cavities (2010/30/EC): 1 Energy efficiency rating: A+

Energy consumption per cycle conventional (2010/30/EC) : 0.87 kWh/

cycle

Energy consumption per cycle forced air convection (2010/30/EC):

0.69 kWh/cycle

Energy efficiency index (2010/30/EC) : 81.2 %

Connection rating: 3600 W Fuse protection: 16 A Voltage: 220-240 V Frequency: 50; 60 Hz

Plug type : no plug (electrical connection by electrician) Included accessories : 2 x combination grid, 1 x universal pan





iQ700, Built-in oven, 60 x 60 cm, Black HB776G1B1B

Features

Features

- Oven with 13 heating methods: 4D hot air, conventional top & bottom heating, hot air grilling, full width grill, half width grill, Pizza setting, coolStart, bottom heat, low temperature cooking, keep warm, plate warming, Hotair gentle, Conventional heat gentle
- Temperature range 30 °C 275 °C
- Cavity volume: 71 litres

Level independent telescopic rails

- 5 shelf positions in oven
- Cavity with shelf support rails, pyrolitic proof

Design

- Touch control
- Cavity inner surface: enamel anthracite

Cleaning

- $\bullet \ active Clean$
- hydrolyse program
- Full glass inner door

Programmes/functions

- Oven Assistant with Voice Control
- SE62
- Electronic oven clock timer
- Digital temperature display with proposal
- Actual temperature display Heating-up indicator
- Drop down oven door, softClose, softOpen
- •
- cookControl Plus
- Fast preheat
- coolStart
- LED light, Light on/off when door opened/closed
- Integral cooling fan
- WLAN Home connect enabled

Accessories

• 2 x combination grid, 1 x universal pan

Features

- Maximum door temperature 30 °C
- Low door temperature during pyrolitic cleaning
- Electronic door lock
- Control panel lock Automatic safety switch off Residual heat indicator Start button Door contact switch

Technical information

- 120 cm Cable length
- Nominal voltage: 220 240 V
- Total connected load electric: 3.6 KW
- Energy efficiency rating (acc. EU Nr. 65/2014): A+
- Energy consumption per cycle in conventional mode:0.87 kWh
- Energy consumption per cycle in fan-forced convection mode:0.69 kWh
- Number of cavities: Main cavity Heat source: electrical Cavity volume:71 litres

Performance/technical information

• Appliance dimension (hxwxd): 595 mm x 594 mm x 548 mm

- Niche dimension (hxwxd): 585 mm 595 mm x 560 mm 568 mm x 550 mm
- Please refer to the dimensions provided in the installation manual



iQ700, Built-in oven, $60 \times 60 \text{ cm}$, Black HB776G1B1B

Dimensioned drawings

If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness		
	fitted	flush	
Induction hob	37 mm	38 mm	
Full surface Induction hob	47 mm	48 mm	
Gas hob	30 mm	38 mm	
Electric hob	27 mm	30 mm	







