

**Series 6, Built-in fridge, 177.5 x 56 cm, soft close flat hinge
KIR81ADD0G**



Included accessories

3 x egg tray, 1 x Heavy-duty hinge support

Optional accessories

KSZGGM00 Butter box

The spacious built-in fridge with VitaFresh XXL drawer for fruit and vegetables and high stability door trays provides optimal food storage.

- **VitaFresh XXL Pro near 0°C:** climate-controlled compartments lock in freshness and nutrients for longer.
- **High-stability door trays:** more height means more flexible space and stability.
- **LED lighting:** all your items in perfect view.
- **Super Cool function:** cools new food faster, to protect what is already inside.
- **MultiBox XXL:** extra-large drawer for your fruit and vegetables.

Technical Data

Energy Efficiency Class:D
 Average annual energy consumption in kilowatt hour per year (kWh/a):91 kWh/annum
 Sum of volume of frozen compartments:0 l
 Sum of volume of chill compartments:310 l
 Airborne acoustical noise emissions :34 dB(A) re 1 pW
 Airborne acoustical noise emission class:B
 Built-in / Free-standing:Built-in
 Door panel options:Not possible
 Height:1772 mm
 Width of the appliance:558 mm
 Depth:548 mm
 Min. required niche size for installation (HxWxD): 1775.0 x 560 x 550 mm
 Net weight:56.8 kg
 Fuse protection:10 A
 Door hinge:Right reversible
 Voltage:220-240 V
 Frequency:50 Hz
 Length electrical supply cord:230.0 cm
 Number of compressors:1
 Number of independent cooling systems:1
 Interior ventilator:Yes
 Reversible Door Hinge:Yes
 Number of Adjustable Shelves in fridge compartment:4
 Shelves for Bottles:Yes
 EAN code:4242005387755
 Brand:Bosch
 Product name / Commercial code:KIR81ADD0G
 Product category:Refrigerator
 Frost free system:No
 Installation typology:Integrated
 Included accessories:3 x egg tray, 1 x Heavy-duty hinge support



Series 6, Built-in fridge, 177.5 x 56 cm, soft close flat hinge KIR81ADD0G

The spacious built-in fridge with VitaFresh XXL drawer for fruit and vegetables and high stability door trays provides optimal food storage.

- Built-in fridge
- Fixed hinge, SoftClosing Door - dampens door movement, for smooth and effortless closure

Performance and Consumption

- EU19_EEK_D: D
- Total Volume : 310 l
- Annual Energy Consumption: 91 kWh/a
- Climate Class: SN-ST
- Noise Level : 34 dB , EU19_Noise emission class_D: B

Functions

- Bright interior LED fridge light

Design features

- LED electronic control
- Optical and accoustical
- Super Cooling: automatic deactivation
- Automatic defrost fridge
- Easy clean interior

Design features

- Net Fridge Volume : 310 l
- 7 safety glass shelves in fridge compartment of which 4 are height adjustable
- 5 door bins
- Metal bottle rack

Freshness System

- 1 VitaFresh drawer with humidity control - Fruits and vegetables retain vitamins and stay fresh for longer
- 1 MultiBox - Transparent drawer with a rippled bottom, ideal for storing fruits and vegetables.

Key features - Fridge section

- Right hinged door, door reversible
- integrated
- Length of power cord: 230 cm
- 220 - 240 V

Dimension and installation

- Niche Dimensions: 177.5 cm H x 56 cm W x 55 cm D
- Dimensions: 177.2 cm H x 55.8 cm W x 54.8 cm D

Key features - Freezer section



- KIR81ADD0G

Country Specific Options

- Based on the results of the standard 24-hour test. Actual consumption depends on usage/position of the appliance.

Additional features

Series 6, Built-in fridge, 177.5 x 56 cm, soft close flat hinge KIR81ADD0G



Maximal permissible weight of the unit fronts

Fitted unit fronts that exceed the permissible weight may cause damage and result in functional impairment of the hinges

Δ Weight

A: Appliance door height including hinges in mm



B: Undamped hinge, unit front in kg

C: Damped hinge, unit front in kg


D: Additional possible load in kg with heavy load kit

A	B	C	D
1500-1750	22	22	
720-1400	19	19	B+5 / C+5
A1	15	19	
A2	15	19	

Measurements in mm




measurements in mm



measurements in mm

Recommended gap dimensions for flat hinges



F	R	X
16-19	0-3	2.5
20	0-1	3
	2-3	2.5
21	0-1	3
	2-3	2.5
22	0	4
	1	3.5
	2-3	3

The gap dimensions recommended in the table must be adhered to in order to ensure that appliance doors do not collide with anything when they are opened, and to avoid causing damage to kitchen units.