

N 70, GAS HOB, 90 CM, STAINLESS STEEL T29CIR8N0



The gas hob with precise flame control, removable dials and pan supports that are suitable for dishwashers - for Comfort Clean.

- $\sqrt{\rm FlameSelect^{\scriptsize (\! R \!)}}$: Gain precise control of your flame.
- $\checkmark\,$ Metallic Sword Dial: Precise and removable for easy cleaning.
- $\checkmark\,$ Cast Iron Pan Supports: For maximum stability and dishwasher cleaning.
- $\checkmark\,$ Dual Wok Burner up to 5.0 kW: Use one gas flame for simmering, two for sizzling stir-fries.
- $\sqrt{}$ Gas Safety Cut-Off: Safety first! No flame, no gas flow.

Z1365WX0 Wireless for Z2402X0 Small pot s

Z2471X0 Z2480X0 Z9404SE0 Z9406SE0 Wireless food thermometer Small pot support Wok ring Simmer plate 4 pieces Set 6 pieces Set

Product name/family:	gas hob w
integrated controls Built-in / Free-standing:	
Energy input:	
Number of cooking zones: Required niche size for installation (HxWxD): .	
490-500 mm	
Width of the appliance:	
Dimensions:	51.5x915x520 mm
Dimensions of the packed product (HxWxD):	165 x 1116 x 659
mm	
Net weight:	16.0 kg
Gross weight:	18.6 kg
Residual heat indicator:	Separate
Location of control panel:	Front
Basic surface material:	Stainless steel
Color of surface:	Stainless steel
Length electrical supply cord:	
EAN code:	4242004284666
Gas connection rating:	12500 W
Fuse protection:	3 A
Voltage:	
Frequency:	





N 70, GAS HOB, 90 CM, STAINLESS STEEL T29CIR8N0

Design

- Stainless steel surface
- black cast iron pan supports with protective rubber feet
- full metal

Usage convenience

- FlameSelect with 9 steps: precisely control and adjust the flame in nine defined levels.
- Design co-ordinated control dials, front: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 5 burner hob
- Including 1 wok burner: use an extra wide power range, separately controlling two flame rings.
- Left front: Economy burner up to 1 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Center front: Wok burner up to 5 KW (depending on gas type)
- Right rear: High speed burner up to 3 KW (depending on gas type)
- \bullet Right front: Standard burner up to 1.75 KW (depending on gas type)

Cleaning

- Removable control dials for easy cleaning between knobs.
- Dishwasher suitable pan supports for easy cleaning.

Safety

• Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): $51.5 \times 915 \times 520$
- Required niche size for installation (HxWxD mm) : 45 x 850 x (490 500)
- Min. worktop thickness: 20 mm
- Power cord: 1 m
- Connected load: 12.5 KW

Accessories

• 1 x WOK attachment ring included



N 70, GAS HOB, 90 CM, STAINLESS STEEL T29CIR8N0

